



FIBER TOOLS

MICRO OPTICAL POWER METER

Essential Tools for the Premise Technician

TESTING | TROUBLESHOOTING | ACCURACY

製品特長:

- 広い測定範囲 (+10~-70dBm)
- 高出力 CATV 範囲 (+26 ~ -50dBm)
- 安全かつ効果的に障害を特定するための VFL
- シングルモードとマルチモードの互換性
- 校正された波長
850/1300/1310/1490/1550/1625nm
- 70Hz、1kHz、2kHzのトーン検出
- オートパワーオフ

内容:

- VFL 付きマイクロ OPM
- ストラップ
- 指示シート

品番:

CAT. NO.	DESCRIPTION
OPM210	VFL を備えたスタンダードパワー OPM
OPM220	VFL を備えたハイパワー OPM
03579	1.25mmアダプター
08325	マイクロOPM用キャリーケース
CAL CERT	校正証明書



TEMPO[®]
COMMUNICATIONS

Renewed Vision. Innovation Forward.



Follow us on Social Media
@TempoComms



FIBER TOOLS

SPECIFICATIONS:

PARAMETER	SPECIFICATIONS	
Model:	OPM210	OPM220
Measurement Range:	-70 to +10dBm (1310/1490/1550/1625)	-50 to +26dBm (1310/1490/1550/1625)
	-60 to +10dBm (850/1300)	-40 to +26dBm (850/1300)
Calibrated Wavelengths:	850, 1300, 1310, 1490, 1550, 1625nm	
Display Resolution:	0.01dB	
Accuracy*:	+/-0.25dB	
Linearity*:	+/-0.5dB (+10 to -3dBm)	+/-0.5dB +26 to -3dBm
	+/-0.1dB (-3 to -50dBm)	+/-0.1dB -3 to -50dBm
	+/-0.5dB (-50 to -70dBm)	
Connector:	Universal 2.5mm	
Wavelength Response:	700 - 1700nm	
Detector:	InGaAs	
Power Supply:	AAA x 2 Alkaline	
Battery Lifetime:	>60 Hours (OPM mode)	
Operating Temperature:	-10 to +50°C (<90% Relative Humidity)	
Storage Temperature:	-20 to +60°C (<90% Relative Humidity)	
VFL Wavelength:	650nm +/-20nm	
VFL Output:	≤ 1mW/ 2Hz	
VFL Range:	4km	
Size:	106 x 58 x 28mm (4.17 x 2.28 x 1.10")	
Weight:	106g (0.23lbs)	
Auto Power Off:	10 minutes of no activity	
Certifications:	CE, RoHS, CDRH, WEEE	

* at -10dBm with FC connector at 23C Specifications subject to change without notice.

1390 Aspen Way Vista, CA • 92081

TC6910 06/21

Latin America Phone : 1.760.510.0558 | EMEA Phone: +44 (0) 1633 927050

©2021 Tempo Communications Inc. • An ISO 9001 Company

EMEA Address: Tempo Communications Limited • Brecon House,
William Brown Close, Cwmbran • NP44 3AB, UK

TempoCom.com | tel 800.642.2155



TEMPO
COMMUNICATIONS

Renewed Vision. Innovation Forward.



Follow us on Social Media
@TempoComms